

## CALIBRATION KITS

## MCAL-1112F 750hm F- female

### Features

- ✓ Standard Kit which includes open-short-load-thru components.
- ✓ Small size, low cost
- ✓ Low VSWR, Stainless Body design

### SPECIFICATIONS

Frequency Range: DC-2500MHz

Impedance: 750hm

Components including: Open / Short / Load/ Through

Connector Type: 75ohm F female

Component Type	MVE P/N	VSWR	Mechanical	Dimensions
<i>Open</i>	MCAL-1112F.O	$\geq 100$	Body: Stainless steel Contact: BE CU, Gold plated	33mm
<i>Short</i>	MCAL-1112F.S	$\geq 100$	Body: Stainless steel Contact: BE CU, Gold plated	33mm
<i>Load</i>	MCAL-1112F.L	<1.02	Body: Stainless steel Contact: BE CU, Gold plated	29mm
<i>Through</i>	MCAL-1112F.T	<1.05	Body: Stainless steel Contact: BE CU, Gold plated	35mm



#### NOTES:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

