

CALIBRATION KITS

MCAL-3300S

3.5mm Female

MCAL-3300SS

3.5mm Male

Features:

- ✓ Standard Kit which includes open-short-load components.
- ✓ Low VSWR
- ✓ Frequency Range: DC to 6 GHz

SPECIFICATIONS:

Components including Open / Short / Load

Electrical Specifications	
Load	VSWR: 1.05:1 MAX.
Open	Phase Deviation $\leq\pm 1^\circ$
Short	Phase Deviation $\leq\pm 1^\circ$
Material	
Load	INNER CONDUCTOR: BERYLLIUM BRONZE, GOLD-PLATED OUTER CONDUCTOR: STAINLESS STEEL, PASSIVATED
Open	INNER CONDUCTOR (FEMALE): BERYLLIUM BRONZE, GOLD-PLATED OUTER CONDUCTOR: STAINLESS STEEL, PASSIVATED
Short	INNER CONDUCTOR (FEMALE): BERYLLIUM BRONZE, GOLD-PLATED INNER CONDUCTOR (MALE): STAINLESS STEEL, PASSIVATED OUTER CONDUCTOR: STAINLESS STEEL, PASSIVATED

Outline Drawing (Unit: mm)



NOTES:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

