


STANDARD COAXIAL CABLE ASSEMBLIES

MVE standard coaxial cable can provide not only inexpensive cost but also a lot of variety models to meet your needs. The overall diameter of flexible series is including, 2.59mm(RG316) , 2.93mm(RG316 Double Shielding), 0.085inch(F085/SS405), 0.141inch(F141/SS402); Semi-flex series are including: 0.085 inch(SF085/RG405), 0.141inch(SF141/RG402); Semi-rigid series are including: 0.034inch(SR034), 0.047 inch(SR047);0.085 inch(SR085); 0.141inch (SR141). In the meantime, MVE can offer customized services and support the optimization of cable assembly. With MVE service, customize product to let user easy to install. MVE is aimed to provide a wide range of performance coaxial cable for various demands.



No	Conn. A/B
10	1.85mm-M
11	1.85mm-F
12	2.4mm-M
13	2.4mm-F
14	2.9mm-M
15	2.9mm-F
16	3.5mm-M
17	3.5mm-F
18	APC7-M
19	APC7-F
20	BNC-M
21	BNC-F
22	MCX-M
23	MCX-F
24	MMCX-M
25	MMCX-F
26	N-M
27	N-F
28	SMA-M
29	SMA-F
30	SSMA-M
31	SSMA-F
32	TNC-M
33	TNC-F
34	MHF202781-M

No	Conn. A/B
35	75ΩBNC-M
36	75ΩBNC -F
37	MHF20311-M
38	75ΩF-M
39	75ΩF-F
40	MHF20367-M
41	MHF20448-M
42	75ΩN-M
43	75ΩN-F
44	75ΩSMB-M
45	75ΩSMB-F
46	MS147-M
47	MM8430-M
48	SMP-F
49	MHF20428-M
50	SMB-F
51	SMB-M
52	UHF-F
53	UHF-M
54	Fakra SMB-M
55	Fakra SMB-F
56	MM8030-M
57	7/16DIN-M
58	MS180-M
59	MS162-M

No	Conn. A/B
60	CRC9-M
61	MS162-M
62	SSMCX-M
63	SMPM-M
64	FAKRA-M
65	TS9A-M
66	MS156C-M
67	MHF20567-M
68	MS156-M
69	MM8930-M
No	Body Style
0	Standard
1	Reverse
2	Right angle
3	Quick
4	RP-Right angle
5	RP-Quick
6	Bulkhead
7	Opposite Direction R/A
8	2Hole Flange
9	RP-Bulkhead
A	Quick/No hex
B	4Hole Flange

No	Coaxial Cables ©
6	RG-6(U)
58	RG58(U)
59	RG59
081	Mini-coaxial 0.81mm
113	Mini-coaxial 1.13mm
137	Mini-coaxial 1.37mm
142	RG-142
174	RG-174
178	RG-178
214	RG-214
316	RG-316
316D	RG-316 Doubt Shield
400	RG-400
F085	SS405
F141	SS402
SF085	RG405
SF141	RG402
SF085JB	RG405(Blue Jacket)
SF141JB	RG402(Blue Jacket)
SPF085	SFL405
SPF141	SFL402
SR034	Semi-rigid 034
SR047	Semi-rigid 047
SR085	Semi-rigid RG405
SR141	Semi-rigid RG402
200LL	200LL,LMR200
400LL	400L,CFD400,LMR400
600LL	600LL,LMR600
2CS	AWG28 x2C
3CS	AWG28 x3C

Code(D)	A	B	C
Tube Type	Brass Tubing	Double Heat-shrink Tubing	Rigid Glued Tubing

COAXIAL CABLE

MCBL-SF141.50

SEMI-FLEX RG402

Features

- ✓ Frequency up to 15GHz
- ✓ Replace to RG402 Cables
- ✓ Excellent shielding effect greater than 110dB



Specifications

CONSTRUCTION		
ITEM	MATERIAL	DIAMETER
CENTER CONDUCTOR	Silver Plated Copper Clad Steel Wire	0.94 mm
DIELECTRIC	PTFE	2.95 mm
OUTER CONDUCTOR	Tin Plated Copper Braid & Tin Soaked	3.53 mm
ELECTRICAL DATA		
ITEM	SPECIFICATION	
OPERATING FREQUENCY	15GHz	
OPERATING TEMP.	- 40°C ~ 165°C	
VELOCITY OF PROPAGATION	69.5%	
CHARACTERISTIC IMPEDANCE	50±2 ohms	
CAPACI-TANCE	94 pF/m	
WORKING VOLTAGE	1900 Vrms (MAX.)	
Weight	41.0 kg / km	
FREQUENCY	ATTENUATION (dB/m)	
1.0 GHz	0.41dB	
2.0 GHz	0.60dB	
3.0 GHz	0.72dB	
5.0 GHz	1.02dB	
10.0 GHz	1.52dB	
15.0 GHz	2.07dB	



NOTES:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY



Cable Assembly Part Number

MVE PART NUMBER	CONNECTOR 1	CONNECTOR 2	XX- LENGTH (cm)	FREQUENCY (GHz)	VSWR (TYP.)
280280.SF141.XX	SMA Male S/T	SMA Male S/T	30, 60, 100,150, 1500	10.0	1.35
280280.SF141.XX(H3)	SMA Male S/T	SMA Male S/T	30, 60, 100, 150	15.0	1.40
280282.SF141.XX	SMA Male S/T	SMA Male R/A	30, 60, 100,150	6.0	1.30
280282.SF141.XX-8G	SMA Male S/T	SMA Male R/A	30, 60, 100,150	8.0	1.35

*Definition of Length: “ XX ”

Length ≤ 30 CM, the length cable is referring to exclude two terminal length of connector.
Length > 30 CM, the length cable is referring to include two terminal length of connector.

**Definition of Tolerance

Length ≤ 10 cm: ± 0.5 cm , Length ≤ 30 cm: ± 1.0 cm , Length ≤ 50 cm: ± 2.0 cm ,
Length ≤ 100 cm: ± 2.5 cm, Length > 101 cm: ± 3.0 cm

***Estimate of Cable Assembly loss

Cable assembly loss =Connector loss + Assembly loss + Cable loss

Connector Loss: $0.08 \times \sqrt{\text{Frequency}} \times 2$ (2 connectors)

Assembly Loss : 0.12×2 (sides)


Cable Loss: per cable attenuation (Max.) * Cable length

NOTES:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

Typical Test Result


PART NUMBER	DESCRIPTION
280280.SF141.100A	SMA Male To SMA Male, Semi-Flex 141 /L:100cm/Brass Tubing




Typical Test Result

PART NUMBER	DESCRIPTION
280280.SF141.200A(H3)	SMA Male To SMA Male, Semi-Flex 141 /L:200cm/Brass Tubing


Tr1 S11 Refl SWR RefLvl: 1 U Res: 100 mU/Div




Tr2 S12 Trans LogM RefLvl: 0 dB Res: 1 dB/Div



Tr3 S21 Trans LogM RefLvl: 0 dB Res: 1 dB/Div




Tr4 S22 Refl SWR RefLvl: 1 U Res: 100 mU/Div




Typical Test Result

PART NUMBER	DESCRIPTION
280282.SF141.150A	SMA Male To SMA Male R/A, Semi-Flex 141 /L:150cm/Brass Tubing


Tr1 S11 Refl SWR RefLvl: 1 U Res: 100 mU/Div



Tr3 S21 Trans LogM RefLvl: 0 dB Res: 1 dB/Div



Tr2 S12 Trans LogM RefLvl: 0 dB Res: 1 dB/Div



Tr4 S22 Refl SWR RefLvl: 1 U Res: 100 mU/Div

